




STRESS RELIE







LEBANON SEABOARD CORPORATION 1600 EAST CUMBERLAND STREET LEBANON, PA 17042 www.lebsea.com

STRESS RELIEF





4-0-10



GUARANTEED ANALYSIS					
Total Nitrogen (N)	4%				
Soluble Potash (K_2O)	10% 8.0%				
8.0% Combined Sulfur (S) Total Iron (Fe)	10%				
Total Manganese (Mn)	2.0%				
Nutrient Sources: Ammonium Sulfate, Sulfate of Potash, Ferrous Sulfate, Ferric Oxide, Manganese Sulfate.					
Chlorine (CI) not more than	2.0% F699				
be removed from these areas promptly after application by sweeping or blowing. Do not wash off with water. Supplemental applications of lawn fertilizer are needed to achieve a minimum 1 pound nitrogen per 1,000 sq. ft.	37				

LEBANON SEABOARD CORPORATION 1600 EAST CUMBERLAND STREET LEBANON, PA 17042 www.lebsea.com

Net Wt. 50 Lbs. (22.68 kg)



DIRECTIONS FOR USE

Apply to turf at a rate of 5 to 10 pounds per 1,000 sq. ft. (for a maximum application rate of 50 pounds per 1,000 sq. ft. per growing season) to generate good color without promoting unwanted top growth. Watering in is recommended for quicker response and better granule dispersion and is particularly recommended when application has been made to moist turf so spotting or staining does not occur. Apply to turf mowed to one-half inch or less only at the lower rate and only after testing to make sure unwanted spotting, staining, or phytotoxicity does not occur. Watering in thoroughly is recommended. Reapply as necessary to maintain desirable color.

ORNAMENTAL USE:

For chlorosis of azaleas, rhododendrons, or evergreens, apply 2 tablespoons of PERK per foot of plant height or 4 pounds per 1,000 sq. ft. Apply uniformly around plant drip zone. Watering in will speed the effects of the product.

For general landscape use, apply 1 tablespoon per foot of plant height or 2 pounds per 1,000 sq. ft. Water in thoroughly to remove any particles from the leaf surface and to activate product.

CAUTION - Iron will stain concrete and clothing. Sweep or blow, do not wash particles off concrete sidewalks. Any clothing that has contacted the product should be washed separately to make sure stains are not transferred to other clothing.

SUGGESTED SPREADER SETTINGS							
	Speed		Speed		Width	Settings	
Spreader	Ground MPH	PTO RPM	of Coverage	5#/1000 Sq. Ft.	10#/1000 Sq. Ft.		
Cyclone	3		8 ft.	4	5½		
Earthway (Rotary)	3		12 ft.	13	18		
Ezee Flow (109)	5	540	30 ft.	C2½	C3½		
Gandy	3			29	34		
Jet-Spred® II Rotary	3		8 ft.	4	5½		
Lely (HR)	5		39 ft.	6½II	71/2II		
Lely (W)	5	425	39 ft.	61/2II	7½II		
Lesco	3		10 ft.	J	М		
Scotts (Drop)	3			5	10		
Scotts (Rotary)	3		6 ft.	Н	L		
Scotts (Rotary) R7X	3		8 ft.	G	J		
Scotts (Rotary) R8A	3		8 ft.	K	N		
Spyker	3		8 ft.	31/2	41/2		
Vicon PS 402	5	540	35 ft.	24	30		

These settings were calibrated and field tested. However, age and condition of spreader, speed of operation, and evenness of terrain may require slightly different settings for desired coverage.

Fertilizer may cause irritation of eyes, nose, throat and skin. In case of contact with skin or eyes, flush with plenty of water; for eyes, get medical attention.

Keep out of reach of children.

CAUTION

LEBANON SEABOARD CORPORATION 1600 EAST CUMBERLAND STREET LEBANON, PA 17042

www.lebsea.com

PERIK* and the Lebanon Diamond are registered trademarks of Lebanon Seaboard Corporation. Iron Humate* is a registered trademark of Kemiron. U.S. Patents 5411569, 5213992, 5902180. Information regarding the contents and levels of metals in this product is available on the Internet at http://www.regulatory-info-lebase.com